# SKG-IKOB PRODUCTCERTIFICATE 637.653.01

Date of issue: 04-02-2019





## Certificate holder

GIESSE S.p.A. Via Tubertini 1 I-40054 Budrio (BO)

T: +39 51 8850677

E: infotechgiesse@schlegel.com

I: www.giesse.it

## **Declaration of SKG-IKOB**

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

rim cam barrel hinge set of 3

delivered under logo / brand:

Giesse

delivered under type- and / or article number:

Domina HP 2 wings/3

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

## SKG-IKOB PRODUCTCERTIFICATE

GIESSE S.p.A. Number: 637.653.01 page 2 of 2

1. PRODUCT PRODUCT TYPE hinge

rim cam barrel hinge set of 3

## 2. TECHNICAL SPECIFICATION

Operating:

Construction: 1 barrel hinge of 2 parts: 1 frame- and 1 leafpart

System:

Material: frame and leaf part: aluminium coated OR anodised

pen: hardened steel

Dimension: frame-part: 51x38x36 mm

leaf-part: 73x38x36 mm

Fixing: direct mounting: 4x M12x55 mm through at least 2 walls of ≥ 1,5 mm

contra plate: 4x M8x55 mm

Intended use: metal, door-inward-opening, door-outward-opening

inside and outside opening aluminium doors and windows

#### 3. DELIVERY

The delivery includes an installation instruction: I05370020QN/01-2019 - I0336002/04-2015

## 4. PERFORMANCES

A rim cam barrel hinge set of 3 according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this rim cam barrel hinge, set of 3 is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this rim cam barrel hinge, set of 3 is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).