



CELERA

CLAMP HINGE FOR ALUMINIUM DOORS

CELERA

For profiles with channel

Celera is the new clamp hinge for doors, in which reliability and quick assembly combine perfectly.



Adjustment

Lateral = ± 1 mm

The adjustment can be made using hex head key (CH 6).



Load capacity

x2 = 100 Kg / x3 = 120 Kg



InstaFit

Celera is supplied with pre-assembled fixing plates and therefore it can be quickly installed on both the sash and frame during the door or window positioning.



Opening

Max 180°



Certification

The hinges are CE marked according to **EN1935** (200,00 cycles) and also applicable on safety exits.



Go to **technical sheet**

Code	Description	Notes	Items per pack
0068101	Celera hinge	Euro groove	20
0068201	Celera hinge	R40	20
0068401	Celera hinge flush outward opening	Euro groove	20
0068501	Celera hinge	Euro groove, 14/18 ALU 16 S9 frame	20
0068701	Celera hinge	R50	20
0068801	Celera hinge	ALLCO 5S	20
0068901	Celera hinge	NC40N	20
0069001	Celera hinge 3 rd Sash	R40	20

InstaFit

Sash hinge

(extruded aluminium)
with pre-assembled
quick fixing plate
(stainless steel).

The **eccentric bush**
is equipped with
an integrated side
adjustment locking
component for easy
and quick insertion
into the hinge.

Frame hinge

(extruded aluminium)
with pre-assembled
quick fixing plate
(stainless steel).

The fixing plates are pre-assembled to the hinge bodies (Giesse RAPID system) thus allowing the installation of an additional hinge without having to dismantle the sash.



The **polyamide cap** ensures that the adjustment remains stable over time.



Washer



Pin Ø 10 mm
(stainless steel).
High burglar
resistance with
the integrated
washer that
prevents pin
removal.



Watch the
video instructions



Schlegel

High performance sealing
solutions



GIESSE

Innovative engineered
hardware



REGUITTI

Italian design handles



DATEC

Timeless exclusive handles

Quanex

GIESSE S.p.A. Via Tubertini 1, 40054 Budrio (BO), Italia
Tel: +39 051 8850000 | email: info.it@quanex.com



U0852201
06/2025