

CHIC 150

Higher load capacity.
Still invisible.

C.H.I.C. 150 BENEFITS



Quick and easy

Fewer components and assembly stages mean faster and simpler production.



180° Opening

C.H.I.C. 150 allows a 180° opening for both side-hung and tilt-and-turn sashes.



150 Kg load capacity

Compatible with most application needs for all housing, residential and public building solutions.



Microventilation

As standard on Tilt-and-Turn. By turning the handle 135° the sash opens by a few millimeters, allowing for a constant air flow that minimizes condensation inside the building.



Adjustable

3D adjustment either in the workshop or after the window has been installed.

Height = -1 / +2,5 mm

Lateral = -1,5 / +1,5 mm

Compression = -0,6 / +1,4 mm



Storage optimisation

With the hardware concealed inside the profile, C.H.I.C. 150 simplifies warehouse organisation by completely eliminating the need to manage finishes.

C.H.I.C. 150 RANGE

Tilt-and-turn

Code	Description	Load capacity	Notes	Microventilation
043651	C.H.I.C. – Kit T/T Hinges + T1 RH arm	150 kg	L = 472 ÷ 700 mm	Yes
043652	C.H.I.C. – Kit T/T Hinges + T1 LH arm	150 kg	L = 472 ÷ 700 mm	Yes
043661	C.H.I.C. – Kit T/T Hinges + T2 RH arm	150 kg	L = 600 ÷ 1500 mm	Yes
043662	C.H.I.C. – Kit T/T Hinges + T2 LH arm	150 kg	L = 600 ÷ 1500 mm	Yes

Side-hung, Secondary sash and Security sash

Code	Description	Load capacity	Notes
043641	C.H.I.C. – Kit T/T Hinges T1	150 kg	L > 300 mm
043642	C.H.I.C. – Kit T/T Hinges T2	150 kg	L > 300 mm
05288	Adjustable fastening element		



WATCH THE
C.H.I.C. VIDEO

